

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 August 2001 (30.08.2001)

PCT

(10) International Publication Number
WO 01/63592 A2

- (51) International Patent Classification⁷: **G10H**
- (21) International Application Number: PCT/US01/05350
- (22) International Filing Date: 20 February 2001 (20.02.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/510,590 22 February 2000 (22.02.2000) US
- (71) Applicant: **HARMONIX MUSIC SYSTEMS, INC.**
[US/US]; 6th floor, 675 Massachusetts Avenue, Cambridge, MA 02139 (US).
- (72) Inventors: **LOPICCOLO, Greg**; 15 Linden Street #6, Brookline, MA 02445 (US). **BELL, Jonathon**; 403 Washington Street #5, Brookline, MA 02446 (US). **EGOZY, Eran**; 14 Meacham Road, Cambridge, MA 02140 (US). **LESSER, Ryan**; 215 Rochambeau Avenue, Providence, RI 02906 (US). **RANDALL, Joshua**; 239 Rawson Road #4, Brookline, MA 02445 (US). **RIGOPULOS, Alexander**; 15 Philemon Street, Arlington, MA 02474 (US). **SCHMIDT, Dan**; 4 Frost Street #1, Cambridge, MA 02140 (US).
- (74) Agent: **LANZA, John, D.**; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 01/63592 A2

(54) Title: METHOD AND APPARATUS FOR DISPLAYING MUSICAL DATA IN A THREE DIMENSIONAL ENVIRONMENT

(57) Abstract: A method for displaying musical data in three dimensions includes displaying musical data along a spatial path that does not lie within the image plane of a display. Graphical symbols corresponding to the musical data may be displayed on graphical surfaces aligned with the spatial path. The graphical surfaces form, in some embodiments, a tunnel through which the time axis associated with the musical data runs. The musical data may be manipulated to provide the viewer with the appearance of motion along the time axis associated with the musical data. In some embodiments, the viewer is represented by a virtual camera in the three-dimensional environment and the virtual camera is "moved" to provide the appearance of motion. A corresponding apparatus is also disclosed.

METHOD AND APPARATUS FOR DISPLAYING MUSICAL DATA IN A THREE DIMENSIONAL ENVIRONMENT

Field of the Invention

The present invention relates to display techniques and, in particular, to techniques for displaying musical information in a three-dimensional environment.

Background of the Invention

5 Music is often defined as “sound organized in time.” Generally speaking, a musical composition is essentially a specified set of musical data parameters and their variation over time. Music notation provides a way for a composer to represent these time-varying musical data visually, such that a musician can interpret the data as instructions and perform the composition as audible music.

10 Several systems exist for visually displaying musical data. One such system is known as “common practice notation” or “CPN.” FIG. 1A depicts an example of music displayed using common practice notation. The musical time axis is represented as a spatial path that proceeds from left to right along the page. The musical data are represented as graphical note symbols plotted on a staff along this path. These note symbols indicate the individual timing, duration,
15 and pitch for each of a series of musical tones. A note’s timing and duration is indicated by its horizontal position along the staff, as well as by its type of note head and stem. A note’s pitch is indicated by its vertical position on the staff. CPN also includes many additional symbols (not shown in FIG. 1A) for indicating various other musical properties such as volume, articulation, etc.

20 Another notation system is known as “piano roll notation” or “PRN.” FIG. 1B depicts an example of music displayed in piano roll notation. The musical time axis is represented as a spatial path that proceeds from top to bottom along the page. Musical data are represented as graphical note symbols plotted along this path. The note symbols (generally vertical bars) indicate the timing, duration, and pitch for each of a series of musical tones. Timing is indicated
25 by the vertical position of the bottom edge of a note. The vertical length of a note indicates duration. Pitch is indicated by the horizontal position of a note. Piano roll notation may also be depicted in horizontal, rather than vertical, format.

- 2 -

Many other systems for visually displaying musical data exist. One property common to all such systems is that they are inherently two-dimensional, i.e., the spatial path representing the musical time axis lies exclusively within the substantially two-dimensional plane of the display surface (referred to throughout as the "image plane"). While these two-dimensional systems for displaying musical data are adequate for conventional applications such as instructing musicians, two-dimensional systems are not ideal for displaying musical data in the context of an interactive gaming environment, because in the state of the art for interactive gaming three-dimensional graphical environments have become the norm.

Summary of the Invention

The present invention provides a method and apparatus for displaying musical data in a three-dimensional environment in which the spatial path corresponding to the musical time axis does not lie within the two-dimensional image plane onto which the three-dimensional environment is rendered. In one embodiment the perception of the viewer is that of traveling along a path in the three-dimensional environment. The path may be straight or curved and, in some embodiments, the path comprises multiple curved segments. This method of displaying musical data provides a viewer with the appearance of navigating through a three-dimensional space, which is a common paradigm for interactive entertainment software such as game software. Thus, the present invention provides a way to represent musical data in a way that is suitable for entertainment purposes.

In one aspect the present invention relates to a method for displaying musical data on the image plane of a provided display. Musical data is displayed in a three-dimensional graphical environment such that a spatial path corresponding to the musical time axis associated with the musical data does not lie within the substantially two-dimensional image plane of the provided display. In some embodiments that spatial path is linear, curved, continuous, or discontinuous. Musical data may be displayed on graphical surfaces aligned with the spatial path. The graphical surfaces form, in some embodiments, a tunnel through which the time axis associated with the musical data runs. In other embodiments the graphical surfaces form a road along which the time axis associated with the musical data runs. The graphic symbols representing the musical data may be manipulated to provide the viewer with the appearance of motion along the time axis associated with the musical data. Alternatively, the virtual "camera" associated with the thee-

- 3 -

dimensional environment may be moved along the time axis associated with the musical data to provide the user with the appearance of motion.

In another aspect, the present invention relates to an apparatus for displaying musical data that includes a display having an image plane and a graphics engine that displays musical data on the display such that a spatial path corresponding to a musical time axis associated with the musical data does not lie in the image plane of the display. In some embodiments, a memory element stores the musical data for display. The graphics engine can display musical data along a spatial path that is linear, non-linear, continuous, or discontinuous. In other embodiments the graphics engine manipulates the graphical symbols associated with the musical data to provide a viewer with the appearance of motion along the time axis associated with the musical data. Alternatively, the graphics engine may change the position of a camera to provide the appearance of motion to the viewer.

In yet another aspect, the present invention relates to a method for displaying musical data on a display having an image plane. A display having an image plane is provided. A time axis associated with musical data is represented as a spatial path through a three-dimensional space. Graphical symbols associated with the musical data are plotted along the spatial axis and the graphical symbols are rendered onto the image plane of the display. In some embodiments, the musical data for display is retrieved from a memory element. In some embodiments that spatial path is linear, curved, continuous, or discontinuous. Musical data may be displayed on graphical surfaces aligned with the spatial path. The graphical surfaces form, in some embodiments, a tunnel through which the time axis associated with the musical data runs. In other embodiments, the graphical surfaces form a road along which the time axis associated with the musical data runs. The graphical symbols representing the musical data may be manipulated to provide the viewer with the appearance of motion along the time axis associated with the musical data. Alternatively, a camera representing the user's position in the three-dimensional environment may be moved to provide the user with the appearance of motion.

Brief Description of the Drawings

The invention is pointed out with particularity in the appended claims. The advantages of the invention described above, together with further advantages, may be better understood by referring to the following description taken in conjunction with the accompanying drawings. In the drawings, like reference characters generally refer to the same parts throughout the different

- 4 -

views. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention.

FIGS. 1A-1B depict musical data represented in common practice notation and piano roll notation, respectively.

5 FIG. 2 is a simplified block diagram of a computer system in which the present invention can be embodied.

FIG. 3 is a perspective view of an embodiment of a three-dimensional space for displaying musical data.

10 FIG. 3A is a perspective view of a three-dimensional space for displaying musical data in which the time axis associated with the musical data extends obliquely from the image plane associated with the display.

FIG. 4A is a perspective view of a three-dimensional space displaying musical data in common practice notation.

15 FIG. 4B is a perspective view of a three-dimensional space displaying musical data as a plurality of bars.

FIG. 5 is a flowchart showing the steps to be taken to represent musical data in a three-dimensional space.

Detailed Description of the Invention

20 When the following specification refers to displaying musical data in a three-dimensional environment, it should be understood that it refers to the illusion of a three-dimensional "virtual" space displayed on a two-dimensional display screen. This effect is achieved by mathematically "rendering" two-dimensional images from objects in a three-dimensional "virtual space" using a "virtual camera," just as a physical camera optically renders a two-dimensional view of real three-dimensional objects. Animation may be achieved by displaying a series of two-
25 dimensional views in rapid succession, similar to motion picture films that display multiple still photographs per second.

Each object in a three-dimensional space is typically modeled as one or more polygons, each of which has associated visual features such as texture, transparency, lighting, shading, anti-aliasing, z-buffering, and many other graphical attributes. The combination of all the polygons
30 with their associated visual features can be used to model a three-dimensional scene. A virtual camera may be positioned and oriented anywhere within the scene. In many cases, the camera is under the control of the viewer, allowing the viewer to scan objects. Movement of the camera

- 5 -

through the three-dimensional space results in the creation of animations that give the appearance of navigation by the user through the three-dimensional environment.

Referring now to FIG. 2, a simplified block diagram of a computer system 14 is shown. A computer system 14 typically will include a central processor 20, a main memory unit 22 for storing programs or data, an input/output (I/O) controller 24, a display device 26, and a data bus 28 coupling these components to allow communication between them. The display device 26 has an image plane that displays images to a viewer. For example, the image plane of a display is the screen of the monitor. The memory 22 includes random access memory (RAM) and read only memory (ROM) chips. The computer 14 typically also has one or more input devices 30 such as a keyboard 32, a mouse 34, or a joystick 12. Other input devices that may be present are mouse pointing devices, trackballs, sliders, faders, game pads or infrared transceivers.

The computer 14 typically also has a hard drive 36 and a floppy drive 38 for receiving floppy disks such as 3.5 inch disks. Other devices 40 also can be part of the computer 14 including output devices (e.g., printer or plotter) and/or optical disk drives for receiving and reading digital data on a CD-ROM. These programs can be loaded onto the hard drive 36 and/or into the memory 22 of the computer 14 via the floppy drive 38. In general, the controlling software program(s) and all of the data utilized by the program(s) are stored on one or more of the computer's storage mediums such as the hard drive 36, CD-ROM 40, etc. In general, the programs implement the invention on the computer 14, and the programs either contain or access the data needed to implement all of the functionality of the invention on the computer 14.

Alternatively, a software graphics engine may be provided which supports three-dimensional scene creation and manipulation. A graphics engine generally includes one or more software modules that perform the mathematical operations necessary to "render" the three-dimensional environment, which means that the graphics engine applies texture, transparency, and other attributes to the polygons that make up a scene. Graphic engines that may be used in connection with the present invention include Realimation, manufactured by Realimation Ltd. of the United Kingdom and the Unreal Engine, manufactured by Epic Games. Although a graphics engine may be executed using solely the elements of a computer system recited above, in many embodiments a graphics hardware accelerator 42 is provided to improve performance. In the embodiment shown in FIG. 2, the graphics accelerator 42 communicates with the central processor 20 over the system bus. In some embodiments, the graphics accelerator 42 communicates directly with the central processor 20 using a processor port. Generally, a

- 6 -

graphics accelerator 42 includes video memory that is used to store image and environment data while it is being manipulated by the accelerator 42.

Graphics accelerators suitable for use in connection with the present invention include: the VOODOO 3 line of graphics boards manufactured by 3dfx Interactive, Inc. of San Jose, California; the RAGE line of graphics boards, manufactured by ATI Technologies, Inc. of Thornhill, Ontario, Canada; the VIPER, STEALTH, and SPEEDSTAR lines of graphics boards manufactured by S3, Inc. of Santa Clara, California; the MILLENIUM line of graphics boards manufactured by Matrox Electronic Systems, Ltd. of Dorval, Quebec, Canada; and the TNT, TNT2, RIVA, VANTA, and GEFORCE256 lines of graphics boards manufactured by NVIDIA Corporation, of Santa Clara, California.

The special abilities of the graphics system are made available to programs via an application programming interface (API). DIRECT3D, a standard API manufactured by Microsoft Corporation of Redmond, Washington may be used and provides some level of hardware independence. The API allows a program to specify the location, arrangement, alignment, and visual features of polygons that make up a three-dimensional scene. The API also allows the parameters associated with a virtual camera to be controlled and changed.

Although various apparatus have been discussed in connection with general-purpose computers, it is well understood by those of ordinary skill in the art that special-purpose hardware performing the same function may also be used.

Referring now to FIG. 3, an embodiment of a three-dimensional "tunnel" for displaying music is shown. In the embodiment shown in FIG. 3, the spatial path corresponding to the time axis 100 associated with music to be displayed extends directly forward from the image plane. Each of the sides 102, 104, 106, 108, 110, 112, 114, 116 form a surface along which graphical symbols corresponding to musical data may be displayed. This data may include information about timbre, pitch, volume, duration, articulation, and any other time-varying aspects of the musical composition being displayed. The graphics engine may access memory element 22 to retrieve data for display. The memory element 22 accessed by the graphics engine may be supplied with musical data from a MIDI file stored on hard drive 36. In other embodiments, the memory element 22 is supplied with musical data directly from an instrument such as a guitar or keyboard. In other embodiments the graphics engine is supplied with data received from a network or generated by a music generation engine, such as those described in commonly-owned

- 7 -

United States Patent Nos. 5,627,335 and 5,763,804, the contents of which are incorporated herein by reference.

Although an octagonal tunnel is depicted in FIG. 3, the three-dimensional tunnel may have any number of sides. In some particular embodiments, the number of sides to be used may be based on the number of viewers of the display. In still other embodiments, the number of sides is based on the number of tracks of musical information to be displayed. For example, a square-shaped three-dimensional tunnel would be sufficient to display four tracks of musical information if a single track is assigned to each surface.

In still other embodiments, the sides do not form a closed shape. The sides may form a road, trough, or some other complex shape that does not have its ends connected to form a closed shape.

In other embodiments, the spatial path corresponding to the musical time axis does not extend perpendicularly from the image plane of the display. FIG. 3A depicts an embodiment of a three dimensional space in which the time axis 100 associated with the music data extends obliquely from the image plane of the display. In further embodiments, the tunnel may be curved or may be some combination of curved portions and straight portions. In still further embodiments, the tunnel may form a closed loop through which the viewer may travel, such as a circular or ellipsoid loop.

As depicted in FIGs. 3 and 3A, each surface may be subdivided into a plurality of segments. Each segment may correspond to some unit of musical time, such as a beat, a plurality of beats, a measure, or a plurality of measures. Although the embodiments shown in FIGs. 3 and 3A show equally-sized segments, each segment may have a different length depending on the particular musical data to be displayed. In addition to musical data, each segment may be textured or colored to enhance the interactivity of the display.

In some embodiments a cursor is provided to indicate which surface is "active," that is, with which surface a viewer can be considered to be musically interacting. In these embodiments, the viewer can use an input device 30 to move the cursor from one surface to another. In further embodiments, the display is used for a multi-player game. In these embodiments, a surface may be colored or textured to identify which user has created the musical data corresponding to the graphical symbols plotted upon that surface.

FIG. 4A depicts a three-dimensional tunnel displaying musical data in common practice notation on two surfaces of the three-dimensional tunnel. Although FIG. 4A depicts musical data

- 8 -

in common practice notation, musical data may be displayed in number of formats. In FIG. 4B musical data is represented by graphical bars 130. Each of the bars displayed in the three dimensional tunnel may indicate a musical event such as the start of a note or a series of notes.

As can be seen from the foregoing figures, the appearance of movement through the three-dimensional space may be simulated by moving the camera along the time axis 100 of the graphical display using the API of the graphics engine. Each API associated with the graphics engines referred to above allow various parameters of the virtual camera to be controlled, including position, orientation, and focal length. Thus, in order to provide the user with the appearance of movement through a three-dimensional environment, the graphics engine is instructed to move the virtual camera through the environment.

In one embodiment, the position of the viewer in the three-dimensional space, and thus the temporal location of the user in the musical score, may be signified by a graphical element. Alternatively, the viewer's position may be signified by graphically altering the graphical symbols representing the musical data. For example, the graphical symbols may flash as the viewer passes by or over them, or they may change color or be highlighted.

As the viewer moves through the three-dimensional space along the spatial path associated with the musical timeline, the musical data represented by associated graphical symbols is substantially simultaneously played as audible music. Thus, in some embodiments, a viewer observes both visual musical output and aural musical output synchronously.

Referring now to FIG. 5, a flowchart showing the steps to be taken to display musical data on a display are shown. In brief overview, the method includes the steps of representing a time axis associated with the musical data as a path through a three-dimensional space (step 502), plotting graphical symbols associated with the musical data along the spatial path (step 504) and rendering the three-dimensional space for display (step 506).

In some embodiments, a display is provided (step not shown). The provided display is any display that supports the drawing of multiple image frames per second, such as a cathode ray tube, liquid crystal display, plasma display or light-emitting diode display. In preferred embodiments, the display supports frame rates of greater than 24 frames per second in order to render movement along the time axis in a fluid fashion.

A time axis associated with musical data is represented as a path through three-dimensional space (step 502). The musical data may be stored in a memory element or it may be received from a network connection or associated input device.

- 9 -

Graphical symbols associated with the musical data are plotted along the spatial path (step 504). For example, in one embodiment the graphical elements are note as used in common practice notation. In other embodiments, the graphical elements are rectangles representing piano roll notation. In still other embodiments the graphical elements are geometric shapes that
5 signal musical events. In still further embodiments related to multi-user games, the graphical elements may be alphanumeric or may indicate the identity of the "owner" of that element.

The musical data is rendered as a two-dimensional view of a three-dimensional environment defined by the stored musical data and the spatial path (step 506). A graphics engine may be used to render the data in response to API commands issued to it by an application
10 program, as described above. In some alternative embodiments, the output may be directed to a network port or to a printer 40.

In some embodiments, no rendering process is used. Instead a three-dimensional environment is simulated using two-dimensional graphical shapes selected and arranged to create the illusion of depth. This technique of simulating three dimensions with two-dimensional
15 graphics is sometimes referred to as "2.5D". It should be understood that 2.5D technique may be used in the present invention as well as true three-dimensional rendering. The present invention may be provided as one or more computer-readable programs embodied on or in one or more articles of manufacture. The article of manufacture may be a floppy disk, a hard disk, a CD-ROM, a flash memory card, a PROM, a RAM, a ROM, or a magnetic tape. In general, the
20 computer-readable programs may be implemented in any programming language, for example, LISP, PERL, C, C++, or PROLOG. The software programs may be stored on or in one or more articles of manufacture as object code.

While the invention has been particularly shown and described with reference to specific preferred embodiments, it should be understood by those skilled in the art that various changes in
25 form and detail may be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

- 10 -

CLAIMS

What is claimed is:

- 1 1. A method for displaying musical data having a musical time axis on a display having an
2 image plane, the method comprising the steps of:
 - 3 (a) representing the musical time axis as a spatial path that does not lie within an
4 image plane of a display; and
 - 5 (b) rendering the spatial path into the image plane.
- 1 2. The method of claim 1 further comprising the step of providing a display having an image
2 plane.
- 1 3. The method of claim 1 wherein step (a) comprises a spatial path that is continuous.
- 1 4. The method of claim 1 wherein step (a) comprises a spatial path that is discontinuous.
- 1 5. The method of claim 1 wherein step (a) comprises a spatial path that is linear.
- 1 6. The method of claim 1 wherein step (a) comprises a spatial path that is non-linear.
- 1 7. The method of claim 1 further comprising the step of displaying graphical symbols
2 corresponding to musical data along the spatial path corresponding to the musical time axis.
- 1 8. The method of claim 7 further comprising the step of manipulating the spatial positions
2 of the graphical symbols associated with musical data to achieve the appearance of motion along
3 the spatial path.
- 1 9. The method of claim 1 further comprising the step of displaying graphical symbols
2 corresponding to musical data along graphical surfaces aligned with the spatial path.
- 1 10. The method of claim 9 wherein the graphical surfaces aligned with the spatial path form a
2 tunnel.
- 1 11. The method of claim 1 further comprising the step of changing the position of a virtual
2 camera to achieve the appearance of motion substantially along the spatial path.
- 1 12. The method of claim 1 further comprising the step of retrieving musical data for display
2 from a memory element.

- 11 -

- 1 13. The method of claim 1 further comprising the step of visually representing the position of
2 the viewer along the musical time axis.
- 1 14. The method of claim 13 further comprising the step of aurally outputting musical data
2 associated with the visual position of the viewer.
- 1 15. An apparatus for displaying musical data comprising:
2 a memory element storing musical data; and
3 a graphics engine, in communication with said memory element, rendering the musical
4 data such that a spatial path corresponding to a musical time axis associated with the
5 musical data does not lie in an image plane of a display.
- 1 16. The apparatus of claim 15 further comprising a display having an image plane.
- 1 17. The apparatus of claim 15 wherein the spatial path is non-linear.
- 1 18. The apparatus of claim 15 wherein the spatial path is discontinuous.
- 1 19. The apparatus of claim 15 wherein said graphics engine changes the position of a virtual
2 camera to provide the appearance of motion along the spatial path.
- 1 20. The apparatus of claim 15 further comprising an audio output device.
- 1 21. A method for displaying musical data on a display having an image plane, the method
2 comprising the steps of:
3 (a) providing a display having an image plane;
4 (b) representing a time axis associated with musical data as a path through a three-
5 dimensional space;
6 (c) plotting graphical symbols associated with the musical data along the spatial path;
7 and
8 (d) rendering the time axis and plotted symbols onto the image plane of the provided
9 display.
- 1 22. The method of claim 21 further comprising the step of retrieving musical data for display
2 from a memory element.

1/7




FIG. 1A





FIG. 1B

2/7



3/7




FIG. 3

4/7




FIG. 3A

5/7




FIG. 4A

6/7




FIG. 4B

7/7




FIG. 5

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
30 August 2001 (30.08.2001)

PCT

(10) International Publication Number
WO 01/63592 A3

(51) International Patent Classification⁷: **G10H 1/00**

SCHMIDT, Dan; 4 Frost Street #1, Cambridge, MA 02140 (US).

(21) International Application Number: PCT/US01/05350

(22) International Filing Date: 20 February 2001 (20.02.2001)

(74) **Agent: LANZA, John, D.**; Testa, Hurwitz & Thibault, LLP, High Street Tower, 125 High Street, Boston, MA 02110 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/510,590 22 February 2000 (22.02.2000) US

(81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(71) **Applicant: HARMONIX MUSIC SYSTEMS, INC.** [US/US]; 6th floor, 675 Massachusetts Avenue, Cambridge, MA 02139 (US).


(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(72) **Inventors: LOPICCOLO, Greg**; 15 Linden Street #6, Brookline, MA 02445 (US). **BELL, Jonathon**; 403 Washington Street #5, Brookline, MA 02446 (US). **EGOZY, Eran**; 14 Meacham Road, Cambridge, MA 02140 (US). **LESSER, Ryan**; 215 Rochambeau Avenue, Providence, RI 02906 (US). **RANDALL, Joshua**; 239 Rawson Road #4, Brookline, MA 02445 (US). **RIGOPULOS, Alexander**; 15 Philemon Street, Arlington, MA 02474 (US).

Published:
— with international search report

[Continued on next page]

(54) **Title: METHOD AND APPARATUS FOR DISPLAYING MUSICAL DATA IN A THREE DIMENSIONAL ENVIRONMENT**



(57) **Abstract:** A method for displaying musical data in three dimensions includes displaying musical data along a spatial path that does not lie within the image plane of a display. Graphical symbols corresponding to the musical data may be displayed on graphical surfaces aligned with the spatial path. The graphical surfaces form, in some embodiments, a tunnel through which the time axis associated with the musical data runs. The musical data may be manipulated to provide the viewer with the appearance of motion along the time axis associated with the musical data. In some embodiments, the viewer is represented by a virtual camera in the three-dimensional environment and the virtual camera is "moved" to provide the appearance of motion. A corresponding apparatus is also discussed.



WO 01/63592 A3



(88) Date of publication of the international search report:
3 January 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/05350

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G10H1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G10H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 99 13455 A (UNIV ILLINOIS) 18 March 1999 (1999-03-18) page 3, line 3 - line 25 page 6, line 11 - line 22 page 17, line 7 - line 25; figure 1 ---	1-9, 15-21
A	US 5 812 688 A (GIBSON DAVID A) 22 September 1998 (1998-09-22) column 4, line 11 -column 5, line 7; figures 4-6 ---	1,2,7-10
A	US 5 952 599 A (DOUGHERTY TOM ET AL) 14 September 1999 (1999-09-14) column 2, line 4 - line 36 column 5, line 50 -column 6, line 29; figures 6,7 --- -/--	1,2,7-9



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

17 September 2001

Date of mailing of the international search report

24/09/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Pulluard, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/05350

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP 0 945 849 A (YAMAHA CORP) 29 September 1999 (1999-09-29)</p> <p>paragraph '0016! - paragraph '0020! paragraph '0057! - paragraph '0059! paragraph '0062! - paragraph '0063!; figure 10</p> <p>---</p>	<p>1-3, 11-16, 19-21</p>
A	<p>DE 197 16 937 A (WAEHNELDT TOBIAS) 26 March 1998 (1998-03-26) page 2, line 37 - line 62; figure 1</p> <p>-----</p>	<p>1,2,15, 21,22</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/05350

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9913455	A	18-03-1999	US 6009394 A AU 9300398 A WO 9913455 A1	28-12-1999 29-03-1999 18-03-1999
US 5812688	A	22-09-1998	NONE	
US 5952599	A	14-09-1999	NONE	
EP 0945849	A	29-09-1999	EP 0945849 A1 JP 11339060 A SG 72937 A1	29-09-1999 10-12-1999 23-05-2000
DE 19716937	A	26-03-1998	DE 19627507 A1 DE 19716937 A1 WO 9722115 A2	19-06-1997 26-03-1998 19-06-1997